

Rondostar 3000.
Versatility
at unmatched prices.



SFS 6115



SFS 6117



SFS 6117 H



SFA 6127 H



SFM 859 H

Compas 3000.
Colorful solutions.

Motostar 3000.
A fast and flexible industrial sheeter.

**A concept
that has no equal,
world-wide.**

Technical Data	Rondostar 3000 SFS 6115	SFS 6117	SFS 6117 H	Compas 3000 SFA 6127 H
Substructure A-frame in stainless steel	painted optional	painted optional	painted optional	stainless steel mobile, rigid substructure with table supports
Automatic dough reeler	without	without	with	with
Automatic flour duster	optional	optional	optional	with
Inlet rollers at safety guards and gas springs				optional
Width of conveyor belts	640 mm	640 mm	640 mm	640 mm
Table length overall	2720 mm	3320 mm	3505 mm	3505 mm
Roller length	660 mm	660 mm	660 mm	660 mm
Safety guard opening	90 mm	90 mm	90 mm	90 mm
Roller gap	0,2-45 mm	0,2-45 mm	0,2-45 mm	0,2-45 mm
Roller gap reduction	Motorized: 50 automatic programmes 9 Man/Auto programmes manual reduction steps	Motorized: 50 automatic programmes 9 Man/Auto programmes manual reduction steps	Motorized: 50 automatic programmes 9 Man/Auto programmes manual reduction steps	Motorized: 50 automatic programmes 20 Man/Auto programmes
Speed of discharge conveyor	85 cm/sec.	85 cm/sec.	85 cm/sec.	50-96 cm/sec.
Rated power	2,0 kVA/1,2 kW	2,0 kVA/1,2 kW	2,0 kVA/1,2 kW	2,0 kVA/1,2 kW
Supply voltage	3x200-420 V, 50/60 Hz	3x200-420 V, 50/60 Hz	3x200-420 V, 50/60 Hz	3x200-420 V, 50/60 Hz
Required floor space: in working position – catch pans extended in resting position	1130x3200 mm 1130x1440 mm	1130x3800 mm 1130x1700 mm	1130x3820 mm 1130x2705 mm	1140x3820 mm 1140x3502 mm
Net weight	225 kg	230 kg	265 kg	360 kg

Technical Data	Motostar 3000 SFM 859 H.A
Substructure stainless steel mobile	rigid, with table supports optional
Automatic reeler	optional
Automatic flour duster	with
Roller opening	0,5-65 mm
Roller reduction	motorized 30 automatic programmes
Roller speed	variable 50-100 m/min.
Infeed belt speed	50-100% of roller speed
Outfeed belt speed	90-100% of roller speed
Roller diameter	146 mm
Roller length	850 mm
Safety guard opening	max. 125 mm
Table length overall	4009 mm
Table width	860 mm
Width of conveyor belts	850 mm
Width of table supports	1050 mm
Required floor space	1381 x 4860 mm
Rated power	8 kVA
Supply voltage	3x200-420V, 50/60 Hz
Net weight	780 kg

Subject to technical changes without notice.
The type specific and the safety instructions of the operating
manuals, as well as the prohibition, mandatory action and
warning signs are to be observed.