

Shaffer® Triple Roller Bar Mixers are ideal for breads, rolls, buns, bagels, English muffins, flour tortillas, pizza crusts, sweet goods, and frozen doughs. The mixer is available in open or enclosed frame designs and is engineered to meet your bakery's specific needs.

Mixer Models 35/70 rpm standard

Model	Capacity		Volume	
	lb	kg	cu ft	L
HS6	600	273	21.2	601
HS8	800	364	23.9	676
HS10	1000	455	27.9	789
HS13	1300	590	36.5	1032
HS16	1600	727	49.9	1414
HS20	2000	909	57.2	1619
HS25	2500	1136	75.0	2124
HS28	2800	1273	81.0	2292
HS32	3200	1458	94.8	2683

Shaffer Innovation & Quality

Shaffer introduced the first open frame (stainless steel tube frame) mixer to the baking industry in 1993 and has over 470 open frame/direct drive mixers in operation today.

Continued on reverse.

BUNDY BAKING SOLUTIONS:

Baking Pans

Release Agents

Pan Coatings & Refurbishment

Equipment & Services

Shaffer® Dough **Processing Equipment**

Dough Pumps & Chunkers


Shaffer® Dough Pumps and Chunkers are ideal for feeding bread, bun, pizza, and similar doughs from the mixer to downstream processing equipment.

Conveyors

Shaffer manufactures vertical, incline, and horizontal conveyors to move dough from the dough pump or chunker to downstream equipment. All conveyors are customized to meet your bakery's needs.



Mixer Designs







Features

- Custom Frame Designs: Enclosed frame, open frame, and open frame hybrid designs available
- Stainless Steel Product Zone: Bowl, agitator, and canopy
- Exclusive Bowl Design: Features more durable bowl sheet, shorter mix times, faster dough development, and cooler doughs
- VerTech® Refrigeration Jacket: Provides superior overall strength, unparalleled ability to absorb dough force, and excellent dough cooling capabilities
- Positive Pressure Side Bowl Seals: Constructed of food-grade material that
 - *Watershed* is a registered trademark of Hoffman Enclosures. Inc.
 - **BFM® fitting is a registered trademark of BFM Global, Ltd.

- forms against canopy to provide exceptional bowl sealing
- Metal Detectable UHMW: Positive pressure front and rear bowl seals
- Rotary Face Agitator Shaft Seals (U.S. Patent No. 10,174,842)
- Hydraulic Bowl Tilt Systems: With jog and tilt using single or dual hydraulic cylinders for forward tilt up to 140° or two-way tilt up to 140° forward and 95° reverse
- Bowl Mounting Bearing: Bowl tilts on a laminate composite bearing
- Watershed® Operator Panel Enclosure:
 Touch screen operator interface. PLC

- controls, and push buttons with universal labels for frequently used functions*
- Heavy Duty Stainless Steel Canopy:
 Butterfly gate with BFM* connector, liquid inlets, and flour dust vent**
- Grout Kit: Anchor bolts and grout for sanitary mixer installation
- NEMA 4X End Doors: On hybrid and enclosed frame models
- NEMA 4 Painted Starter Enclosure
- · UL, cUL Compliant Controls
- BISSC Certified
- · ANSI, USDA, and CE Compliant

Optional Features

- · Sanitary Bowl Drain
- Refrigerated Agitator (U.S. Patent No. 9,295,956)
- · Refrigerated Breaker Bar
- · Sliding Flour Gate
- · Ingredient or Sponge Door

- Custom Operator Interface and PLC Packages
- · U-shape Bowl
- · Y-T Asymmetrical (Stant Bar) Agitator
- · NEMA 4X Stainless Steel Starter Enclosure
- Grace Port 120 VAC Outlet and Ethernet Port in Electrical Enclosure Door
- Non-Contact Voltage Detector and Voltage Indicator in Electrical Enclosure Door
- · Load Cells
- · ARC Flash Protected Main Circuit Breaker
- · Trough, Pump, or Chunker Locks
- Special Ingredient Inlets







For additional information or to request a quote, call +1.937.652.2151 or email info@shaffermixers.com.

