

BEcom BREAD LINES



COMPLETE BREAD LINES



BEcom BREAD LINES



COMPLETE BREAD LINES

The BEcom Complete Bread Line consists of:

- Volumetric Divider (BE-VDIV-2400)
- Conical Rounder (BE-CONR-RB)
- Intermediate Proofer (BE-IP SERIES)
- Long Moulder (BE-LM)

| MODEL | POCKET QUANTITY |
|----------------------------------|-----------------|
| COMPLETE BREAD LINE - 88 POCKET | 88 |
| COMPLETE BREAD LINE - 152 POCKET | 152 |
| COMPLETE BREAD LINE - 176 POCKET | 176 |
| COMPLETE BREAD LINE - 240 POCKET | 240 |
| COMPLETE BREAD LINE - 328 POCKET | 328 |
| COMPLETE BREAD LINE - 640 POCKET | 640 |

| MODEL | CAPACITY (QTY/HR) | WORKING RANGE (PISTON DIA/OZ) | DIMENSIONS | WEIGHT | POWER |
|--|-------------------|-------------------------------|-----------------|---------|----------------------------|
| BE-VDIV-2400-M | 1200 - 2400 | 3" / 2-7 oz | 55" x 37" x 62" | 992 lbs | 208V - 3Ph - 60Hz - 4 AMPS |
| | | 4" / 4-21 oz | | | |
| | | 5" / 9-35 oz | | | |
| BE-VDIV-2400-C <i>(With PLC Control Screen)</i> | 1200 - 2400 | 3" / 2-7 oz | 55" x 37" x 62" | 992 lbs | 208V - 3Ph - 60Hz - 4 AMPS |
| | | 4" / 4-21 oz | | | |
| | | 5" / 9-35 oz | | | |

| MODEL | CAPACITY (QTY/HR) | DOUGH WEIGHT | DIMENSIONS | WEIGHT | POWER |
|------------|-------------------|--------------|-----------------|---------|------------------------------|
| BE-CONR-RB | 1000 - 2400 | 4 - 42 oz | 41" x 37" x 56" | 430 lbs | 208V - 3Ph - 60Hz - 1.5 AMPS |

| MODEL | POCKET QUANTITY | ENTER/EXIT DIMENSIONS (C x D) | PROOFING TIME (MIN.SEC) | DIMENSIONS (A x B x H) | WEIGHT | POWER |
|-----------|-----------------|-------------------------------|-------------------------|------------------------|----------|----------------------------|
| BE-IP-88 | 88 | 32" / 37" x 61" | 2 - 4 Min | 42" x 48" x 98" | 882 lbs | 208V - 3Ph - 60Hz - 5 AMPS |
| BE-IP-152 | 152 | 32" / 37" x 49" | 3.3 - 7.2 Min | 42" x 78" x 83" | 992 lbs | 208V - 3Ph - 60Hz - 5 AMPS |
| BE-IP-176 | 176 | 32" / 37" x 61" | 4.2 - 8.4 Min | 42" x 78" x 98" | 1213 lbs | 208V - 3Ph - 60Hz - 5 AMPS |
| BE-IP-240 | 240 | 32" / 37" x 49" | 6 - 12 Min | 61" x 78" x 83" | 1102 lbs | 208V - 3Ph - 60Hz - 5 AMPS |
| BE-IP-328 | 328 | 32" / 37" x 61" | 8 - 16 Min | 61" x 78" x 98" | 1542 lbs | 208V - 3Ph - 60Hz - 5 AMPS |

| MODEL | POCKET QUANTITY | ENTER/EXIT DIMENSIONS (C x D) | PROOFING TIME (MIN.SEC) | DIMENSIONS (A x B x H) | WEIGHT | POWER |
|-----------|-----------------|-------------------------------|-------------------------|------------------------|----------|------------------------------|
| BE-IP-640 | 640 | 23" x 69" | 5-15 Min | 116" x 71" x 94" | 1984 lbs | 208V - 3Ph - 60Hz - 2.4 AMPS |

| MODEL | MAX CAPACITY (QTY/HR) | MAX DOUGH LENGTH | PRESSURE PLATE LENGTH | DIMENSIONS | WEIGHT | POWER |
|-------|-----------------------|------------------|-----------------------|-----------------|---------|------------------------------|
| BE-LM | 2400 | 17" | 37" | 27" x 65" x 54" | 518 lbs | 208V - 3Ph - 60Hz - 1.5 AMPS |

