

ELECTRICAL OPTIONS

- PLC other than standard
- Inverter other than standard
- PLC upgrade for conveyor control from pump
- Remote cleaning starter box
- Quick disconnect power plug assembly
- Pump mounted operator control box option
- CE electrical package
- Stainless steel remote electrical panel in lieu of painted steel



Optional Pump Mounted Station

SPECIFICATIONS

Model	Hopper Size*	Length**	Width**	Height**	Approximate Shipping Weight
8	800 lb. (363 kg)	47" (1194 mm)	34" (864 mm)	26" (660 mm)	2,050 lb. (930 kg)
10	1,000 lb. (454 kg)	51.75" (1314 mm)	34" (864 mm)	28" (711 mm)	2,150 lb. (975 kg)
13	1,300 lb. (590 kg)	54.75" (1391mm)	34" (864 mm)	32" (813 mm)	2,250 lb. (1021 kg)
16	1,600 lb. (726 kg)	57.50" (1461 mm)	34" (864 mm)	35.50" (902 mm)	2,350 lb. (1066 kg)
20	2,000 lb. (907 kg)	57.50" (1461 mm)	40" (1016 mm)	35.50" (902 mm)	2,450 lb. (1111 kg)
24	2,400 lb. (1089 kg)	57.50" (1461 mm)	48.50" (1232 mm)	35.88" (911 mm)	2,550 lb. (1157 kg)
28	2,800 lb. (1270 kg)	60" (1524 mm)	48.50" (1232 mm)	40" (1016 mm)	2,600 lb. (1179 kg)
32	3,200 lb. (1452 kg)	62.50" (1588 mm)	48.50" (1232 mm)	42" (1067 mm)	2,650 lb. (1202 kg)

* Hopper size calculated at 69 lb./ft³

** See drawing on back cover. Custom sizes available.

Electrical Requirements	
Approximate Main Power	
5 HP	5 KVA
7.5 HP	12 KVA
10 HP	15 KVA
15 HP	22 KVA
20 HP	28 KVA
25 HP	33 KVA
30 HP	41 KVA

No air required

Drive (HP)	Maximum Throughput*
5	2,500 lb./hr. (1134 kg)
7.5	3,750 lb./hr. (1701 kg)
10	5,000 lb./hr. (2268 kg)
15	7,500 lb./hr. (3402 kg)
20	10,000 lb./hr. (4536 kg)
25	12,500 lb./hr. (5670 kg)
30	15,000 lb./hr. (6804 kg)

* May be reduced when handling unusually stiff doughs