



Item No. _____
 Project _____
 Quantity _____

BakerSeries Electric "Mini" Rotating Rack Oven

MODEL: LMO-E - Series



Model LMO-E8S Shown

MODEL / RACK CAPACITY

	LMO-G6	LMO-G8
18 x 26 Sheet Pans	6	8
12" x 20" Hotel Pans	6	8
Pan Bread 16oz Loaves	30	N/A
8 Oz. Baguettes	30	40
Cookies 2 oz.	12 Doz.	16 Doz.

Short Bid Specification:

Oven shall be electrically heated LBC Mini Rack Oven, model no. **LMO-E** [insert 6-208, 6-240, 6-480, 8-208, 8-240, 8-480, 6S-208, 6S-240, 6S-480, 8S-208, 8S-240, 8S-480] with capacity for 6 or 8 18" x 26" sheet pans. The oven shall operate on 208, 240 or 480 VAC 3-Phase [specify at time of order]. The oven shall have an internal steam system consisting of 150 pounds of steel bars and a water drop system that dispenses water to the steel mass through multiple large holes in a stainless steel tube located over the steel mass. The oven shall be electrically heated using Incoloy sheathed elements. The oven shall be mounted on a stainless steel stand having front mounted heavy duty locking swivel casters and rear mounted stationary locking casters or shall be mounted on 8" stainless steel legs. The oven shall have an optional proofer base having front mounted heavy duty locking swivel casters and rear mounted stationary locking casters.

STANDARD PRODUCT WARRANTY

One-Year Parts and Labor (contiguous US Including Alaska and Hawaii, Canada)

Construction Features

- . Heavy duty stainless steel interior and exterior
- . Incoloy sheathed heater elements
- . 150 Lbs. Thermal Mass
- . Low pressure water injection steam system
- . Full-view double pane door window
- . Hinged inner glass window for easy cleaning
- . Full perimeter silicone door seal
- . Mechanical door latch with magnetic closer
- . Field connection point for hood proving switch

Performance Features

- . Fast acting heater elements
- . 0.75 GPH water delivery system
- . 10/20 second normal steam time
- . Safety limited torque drive rotation system
- . Low noise air circulation system
- . Brightly lit interior
- . Fast acting programmable vent

Controls Features

- . Large LED display for time, temperature and steam
- . Simple manual setting for temperature, time, steam
- . Manual one-touch venting control
- . Manual blower one-touch delay or pulse blower
- . Storage for up-to 99 programmed recipes
- . 6-button quick access recipe menu



Meets UL 197 and NSF-4 Standards

Sheet Number LMO-E (rev 03/08)