



Item No. _____
 Project _____
 Quantity _____

BakerSeries Triple Wide Roll-in Proofer

MODEL: LRP3 - Series



Model LRP3-40 Shown

MODEL / RACK CAPACITY

Model / Depth	Side Load	End Load	Double
LRP3-30	3 Racks	4 Racks	None
LRP3-40	6 Racks	4 Racks	3 racks
LRP3-50	8 Racks	7 Racks	3 Racks
LRP3-60	10 racks	8 Racks	4 Racks
LRP3-70	10 Racks	10 Racks	5 Racks
LRP3-80	13 Racks	11 Racks	6 Racks
LRP3-90	15 Racks	12 Racks	6 Racks
LRP3-100	15 Racks	14 Racks	7 Racks
LRP3-110	18 Racks	16 Racks	8 Racks
LRP3-120	20 Racks	17 Racks	9 Racks

Short Bid Specification:

Proofer shall be an **LBC Bakery Equipment Model LRP3-** [insert 30, 40, 50, 60, 70, 80, 90, 100, 110, 120] 5 to 13.2kW electrically heated, double door, triple-wide roll-in rack unit with: quick responding air-wash heat / humidity system; modular foam insulated cam lock panel construction; all 300 series stainless steel interior, with protective cart bumpers; heavy-duty door with magnetic seal/mechanical closure system and full width protective bar handle; simple computerized controls, door mounted at eye-level, with accurate digital temperature, humidity and time readouts; plus all the features listed and options checked.

STANDARD PRODUCT WARRANTY

One-Year Parts and Labor (contiguous US Including Alaska and Hawaii, Canada)

Construction Features

- . Two Door, triple wide rack capacity
- . Heavy duty stainless steel exterior with 300 Series stainless steel interior and aluminized steel top
- . Walls Ceilings and doors are foam insulated
- . Modular wall and ceiling panels with cam lock construction
- . Rapid responding air-wash heat and humidity system
- . 208/240 VAC single or 3-phase power, field convertible

Performance Features

- . 70 - 120 Degree F proofing range
- . 50 - 99% humidity range
- . Non-submerged calrod type heaters
- . Interior bumpers protect interior walls from damage
- . Lighted interior

Controls Features

- . All digital controls mounted in the door at eye-level
- . PID Type controls for rapid accurate response without overshoot
- . Digital set Temperature, Humidity, Time
- . Installed in the left hand door at eye-level
- . Large LED displays



Meets UL 763 and NSF-8 Standards

Sheet Number LRP3 v 8 (rev 07/06)