

RW1548 SPECIFICATIONS

OVERALL DIMENSIONS

WIDTH = 56-3/4" DEPTH = 65"
HEIGHT (OVERALL) = 92-1/2" (94-1/2" GAS)
HEIGHT (PIT MODEL) = 81-1/2" ABOVE FLOOR
DOOR OPENING = 31" WIDE x 77" HIGH

HOT WATER SYSTEM

1" HOT WATER SUPPLY REQUIRED, UNION PROVIDED
140° F. WATER REQUIRED AT THE MACHINE
168 GPH AT 20 PSI (14 GAL./CYCLE x 12 CYCLES/HR.)
RINSE BOOSTER: TWO 9 kW HEATING ELEMENTS IN A 20 GAL. RINSE TANK

FULL LOAD AMPS

	208 VOLT	230 VOLT	460 VOLT
ELECTRIC	133.1	122.3	62.1
GAS/STEAM (INJECTED)	95.6	88.4	45.2
STEAM (RECIRCULATING)	45.6	43.2	22.6

GAS SYSTEM (GAS MACHINES ONLY)

1/2" GAS SUPPLY
NATURAL: 7" W.C. MINIMUM INLET, 6" W.C. MAIN MANIFOLD = 66,000 BTU
PROPANE: 11" W.C. MINIMUM INLET, 10" W.C. MAIN MANIFOLD = 66,000 BTU
4" STAINLESS STEEL CHIMNEY ON SIDE OF MACHINE

STEAM SYSTEM (STEAM MODELS ONLY)

3/4" STEAM LINE, 1015 PSI – 37 LBS. PER HOUR AVERAGE - INJECTED
76 LBS. PER HOUR AVERAGE - RECIRCULATING

WASH SYSTEM

10 HP & 5 HP PUMPS IN SERIES RECIRCULATE APPROXIMATELY 240 GPM @ 60 PSI

HEAT: >ELECTRIC – ONE 9 kW AND ONE 4.5 kW HEATING ELEMENT
>GAS – THREE 22,000 BTU RATED INFRARED BURNERS = 66,000 BTU
>STEAM – DIRECT INJECTION, 10-15 PSI, 37 LBS. PER HOUR AVERAGE
RECIRCULATED, 10-15 PSI, 76 LBS. PER HOUR AVERAGE

65 GALLON WASH TANK
1-1/2" COPPER DRAIN
8" STEAM EXHAUST VENT COMPANION FLANGE